

```

<?xml version="1.0" encoding="UTF-8" ?>
<!DOCTYPE aspect_oriented_model (View Source for full doctype...)>
- <aspect_oriented_model>
  - <goal_model id="GM1" name="Manage [health service]">
    <softgoal id="G1" name="Make [health service] better"
      decomposition_label="and" />
  - <goal id="G2" name="Manage [health service]" decomposition_label="and">
    - <goal id="G3" name="Manage [complaints] and [notifications]"
      decomposition_label="and">
    - <task id="T3.1" name="Specify [complaint]"
      decomposition_label="and">
      - <task id="T3.1.1" name="Select [kind of complaint]"
        decomposition_label="and">
        <task id="T3.1.1.1" name="Select [diverse complaint]"
          decomposition_label="or" />
        <task id="T3.1.1.2" name="Select [food complaint]"
          decomposition_label="or" />
        <task id="T3.1.1.3" name="Select [animal complaint]"
          decomposition_label="or" />
      </task>
      <task id="T3.1.2" name="Register [kind], [date], [time] of the
        [complaint]" decomposition_label="and" />
      <task id="T3.1.3" name="Request [complaint information]"
        decomposition_label="and" />
      <task id="T3.1.4" name="Register [generic complaint
        information]" decomposition_label="and" />
      <task id="T3.1.5" name="Register [diverse complaint
        information]" decomposition_label="or" />
      <task id="T3.1.6" name="Register [food complaint
        information]" decomposition_label="or" />
      <task id="T3.1.7" name="Register [animal complaint
        information]" decomposition_label="or" />
      <task id="T3.1.8" name="Show [complaint code]"
        decomposition_label="and" />
    </task>
  - <task id="T3.2" name="Update [complaint]"
    decomposition_label="and">
    <task id="T3.2.1" name="Request [complaint code]"
      decomposition_label="and" />
    <task id="T3.2.2" name="Show [complaint information]"
      decomposition_label="and" />
    <task id="T3.2.3" name="Request [conclusion]"
      decomposition_label="and" />
    <task id="T3.2.4" name="Register [conclusion], [date] and
      [employee] who gave conclusion"
      decomposition_label="and" />
  </task>
</goal>
- <goal id="G4" name="Make [information on health service] available"
  decomposition_label="and">
  - <task id="T4.1" name="Register [tables]"
    decomposition_label="and">
    - <task id="T4.1.1" name="Register [health unit]"
      decomposition_label="and" />
      <task id="T4.1.1.1" name="Register [unit code and unit
        description]" decomposition_label="and" />
    </task>
  </task>

```

```

- <task id="T4.1.2" name="Register [speacialty]"
  decomposition_label="and">
  <task id="T4.1.2.1" name="Register [code and description]"
    decomposition_label="and" />
</task>
- <task id="T4.1.3" name="Register [employee]"
  decomposition_label="and">
  <task id="T4.1.3.1" name="Register [login, name and
    password]" decomposition_label="and" />
</task>
- <task id="T4.1.4" name="Register [disease]"
  decomposition_label="and">
  <task id="T4.1.4.1" name="Register [code, name,
    description, symptom and duration]"
    decomposition_label="and" />
</task>
- <task id="T4.1.5" name="Register [symptom]"
  decomposition_label="and">
  <task id="T4.1.5.1" name="Register [code and description]"
    decomposition_label="and" />
</task>
</task>
- <task id="T4.2" name="Query [information]"
  decomposition_label="and">
- <task id="T4.2.1" name="Query [health guide information]"
  decomposition_label="or">
- <task id="T4.2.1.1" name="Query [health units] that take
  care of a specific [specialty]" decomposition_label="or">
  <task id="T4.2.1.1.1" name="Select [specialty]"
    decomposition_label="and" />
</task>
- <task id="T4.2.1.2" name="Query [specialties] of a [health
  unit]" decomposition_label="or">
  <task id="T4.2.1.2.1" name="Select [unit]"
    decomposition_label="and" />
</task>
- <task id="T4.2.2.2" name="Query [diseases]"
  decomposition_label="or">
  <task id="T4.2.2.2.1" name="Select [disease]"
    decomposition_label="and" />
  <task id="T4.2.2.2.2" name="Show [disease]"
    decomposition_label="and" />
</task>
</task>
- <task id="T4.2.2" name="Query [complaints]"
  decomposition_label="or">
  <task_ref id="T3.2.1" decomposition_label="and" />
  <task_ref id="T3.2.2" decomposition_label="and" />
</task>
</task>
</goal>
</goal>
- <correlation_relationship label="help">
- <source>
  <goal_ref id="G2" decomposition_label="and" />
</source>
- <target>

```

```

        <softgoal_ref id="G1" decomposition_label="and" />
    </target>
</correlation_relationship>
</goal_model>
- <goal_model id="GM15" name="Persistence">
- <goal id="G15.1" name="Persistence" decomposition_label="and">
- <task id="T15.1.1" decomposition_label="and" name="Persistence in
[DB]">
    <task id="T15.1.1.7" name="Persistence in [Microsoft Access]"
decomposition_label="or" />
    <task id="T15.1.1.5" name="Persistence in [Oracle]"
decomposition_label="or" />
    <task id="T15.1.1.6" name="Persistence in [MySQL]"
decomposition_label="or" />
- <task id="T15.1.3" decomposition_label="and" name="Make register
operation">
    <task id="T15.1.3.1" name="Insert [data]"
decomposition_label="or" />
    <task id="T15.1.3.2" name="Search [data]"
decomposition_label="or" />
    <task id="T15.1.3.3" name="Delete [data]"
decomposition_label="or" />
    <task id="T15.1.3.4" name="Update [data]"
decomposition_label="or" />
    <task id="T15.1.3.5" name="Print [data]"
decomposition_label="or" />
    </task>
</task>
</goal>
- <crosscutting_relationship>
- <source>
    <task_ref id="T15.1.1" decomposition_label="and" />
</source>
- <pointcut id="P15.1" name="make register operation">
- <pointcut_expression>
- <operand primitive="include">
    <regular_expression text="Register.*" param="name"
type="task" />
</operand>
<and />
- <pointcut_expression>
    <not />
- <operand primitive="include">
    <task_ref id="T4.1" decomposition_label="and" />
</operand>
</pointcut_expression>
</pointcut_expression>
</pointcut>
- <pointcut id="P15.2" name="set DB">
- <pointcut_expression>
- <operand primitive="include">
    <softgoal_ref id="S3.2" decomposition_label="and" />
</operand>
</pointcut_expression>
</pointcut>
- <intertype_declaration type="element">

```

```

- <a_it_expression>
  <pointcut_ref id="P15.2" />
</a_it_expression>
- <intertype_declaration_body>
  - <task id="T3.1.2.4" decomposition_label="make" name="Set
[DB]">
    <task id="T3.1.2.10" name="Select [Microsoft Access]"
      decomposition_label="or" />
    <task id="T3.1.2.11" name="Select [Oracle]"
      decomposition_label="or" />
    <task id="T3.1.2.12" name="Select [MySQL]"
      decomposition_label="or" />
  </task>
</intertype_declaration_body>
</intertype_declaration>
- <advice type="around">
  - <a_it_expression>
    <pointcut_ref id="P15.1" />
  </a_it_expression>
  - <advice_body>
    <task_ref id="T15.1.3" decomposition_label="and" />
  </advice_body>
</advice>
</crosscutting_relationship>
</goal_model>
- <goal_model id="GM5" name="Error and Exception Handling">
  <softgoal id="S5.1" name="Error and Exception Handling"
    decomposition_label="and" />
- <goal id="G5.2" name="Handling [exception]" decomposition_label="and">
  <task id="T5.2.1" decomposition_label="and" name="Detect
[exception]" />
  <task id="T5.2.4" decomposition_label="and" name="Apply
[handler]" />
</goal>
- <crosscutting_relationship>
  - <source>
    <task_ref id="T5.2.1" decomposition_label="and" />
  </source>
  - <pointcut id="PC5.3" name="persistence">
    - <pointcut_expression>
      - <operand primitive="include">
        <task_ref id="T15.1.1" decomposition_label="and" />
      </operand>
    </pointcut_expression>
  </pointcut>
  - <pointcut id="PC5.4" name="authentication">
    - <pointcut_expression>
      - <operand primitive="include">
        <task_ref id="T9.3.3" decomposition_label="and" />
      </operand>
    </pointcut_expression>
  </pointcut>
  - <pointcut id="PC5.5" name="availability">
    - <pointcut_expression>
      - <operand primitive="include">
        <softgoal_ref id="S9.3" decomposition_label="and" />
      </operand>
    </pointcut_expression>
  </pointcut>

```

```

        </operand>
    </pointcut_expression>
</pointcut>
- <intertype_declaration type="element">
    - <a_it_expression>
        <pointcut_ref id="PC5.3" />
    </a_it_expression>
    - <intertype_declaration_body>
        <task id="T5.2.1.3" name="Detect [persistence exception]" decomposition_label="and" />
    </intertype_declaration_body>
</intertype_declaration>
- <intertype_declaration type="element">
    - <a_it_expression>
        <pointcut_ref id="PC5.4" />
    </a_it_expression>
    - <intertype_declaration_body>
        <task id="T5.2.1.1" name="Detect [authentication exception]" decomposition_label="and" />
    </intertype_declaration_body>
</intertype_declaration>
- <intertype_declaration type="element">
    - <a_it_expression>
        <pointcut_ref id="PC5.5" />
    </a_it_expression>
    - <intertype_declaration_body>
        <task id="T5.2.1.2" name="Detect [availability exception]" decomposition_label="and" />
    </intertype_declaration_body>
</intertype_declaration>
</crosscutting_relationship>
- <correlation_relationship label="help">
    - <source>
        <softgoal_ref id="S5.1" decomposition_label="and" />
    </source>
    - <target>
        <softgoal_ref id="G1" decomposition_label="and" />
    </target>
</correlation_relationship>
- <correlation_relationship label="make">
    - <source>
        <goal_ref id="G5.2" decomposition_label="and" />
    </source>
    - <target>
        <softgoal_ref id="S5.1" decomposition_label="and" />
    </target>
</correlation_relationship>
</goal_model>
- <goal_model id="GM9" name="Security">
    - <softgoal id="S9.0" name="Security" decomposition_label="and">
        - <softgoal id="S9.3" name="Availability" decomposition_label="make">
            <goal id="G9.3.1" name="The system should be available 24 hours a day, 7 days a week." decomposition_label="and" />
            <goal id="G9.3.2" name="Because of the nature of not being a critical system, the system might stay off until any fault is fixed." decomposition_label="and" />
        </softgoal>
    </softgoal>
</goal_model>

```

```

        </softgoal>
    </softgoal>
    - <goal id="G9.3" name="Authentication" decomposition_label="and">
        <task id="T9.3.3" name="Authentication by Login"
            decomposition_label="and" />
    - <task id="T9.3.4" name="Validate [data]" decomposition_label="and">
        <task id="T9.3.4.2" name="Compare [data] with [credentials]"
            decomposition_label="and" />
    </task>
    - <goal id="G9.3.5" name="Authorization" decomposition_label="and">
        - <task id="T9.3.5.1" name="Control [access]"
            decomposition_label="and">
                <task id="T9.3.5.1.1" name="Restrict [access] to [functions]"
                    decomposition_label="and" />
                <task id="T9.3.5.2.2" name="Restrict [access] to [data]"
                    decomposition_label="and" />
            </task>
        </goal>
    - <correlation_relationship label="make">
        - <source>
            <softgoal_ref id="G9.3" decomposition_label="and" />
        </source>
        - <target>
            <softgoal_ref id="S9.0" decomposition_label="and" />
        </target>
    </correlation_relationship>
    - <crosscutting_relationship>
        - <source>
            <goal_ref id="G9.3" decomposition_label="and" />
        </source>
        - <pointcut id="P9.3.1" name="authentication">
            - <pointcut_expression>
                - <operand primitive="include">
                    <task_ref id="T3.2" decomposition_label="and" />
                </operand>
                <and />
                - <operand primitive="include">
                    <task_ref id="T4.1" decomposition_label="and" />
                </operand>
            </pointcut_expression>
        </pointcut>
        - <advice type="around">
            - <a_it_expression>
                <pointcut_ref id="P9.3.1" />
            </a_it_expression>
            - <advice_body>
                <task_ref id="T9.3.3" decomposition_label="and" />
            </advice_body>
        </advice>
    </crosscutting_relationship>
</goal>
- <goal id="G9.2" name="Encryption" decomposition_label="and">
    <task id="T9.2.3" name="Encryption Algorithm"
        decomposition_label="and" />
    - <task id="T9.2.5" name="Make [Encryption operations]"
        decomposition_label="and" />

```

```

<task id="T9.2.1" name="Encrypt [data]"
    decomposition_label="and" />
<task id="T9.2.2" name="Decrypt [data]"
    decomposition_label="and" />
</task>
- <correlation_relationship label="help">
  - <source>
    <goal_ref id="G9.2" decomposition_label="and" />
  </source>
  - <target>
    <softgoal_ref id="S9.0" decomposition_label="and" />
  </target>
</correlation_relationship>
- <crosscutting_relationship>
  - <source>
    <goal_ref id="G9.2" decomposition_label="and" />
  </source>
- <pointcut id="PC9.3.5.1" name="Symetric">
  - <pointcut_expression>
    - <operand primitive="include">
      <task_ref id="T9.3.3" decomposition_label="and" />
    </operand>
  </pointcut_expression>
</pointcut>
- <advice type="around">
  - <a_it_expression>
    <pointcut_ref id="PC9.3.5.1" />
  </a_it_expression>
  - <advice_body>
    <task_ref id="T9.2.3" decomposition_label="and" />
  </advice_body>
</advice>
</crosscutting_relationship>
</goal>
- <correlation_relationship label="help">
  - <source>
    <softgoal_ref id="S9.0" decomposition_label="and" />
  </source>
  - <target>
    <goal_ref id="G2" decomposition_label="and" />
  </target>
</correlation_relationship>
</goal_model>
- <goal_model id="GM10" name="Performance">
  <softgoal id="S10.1" name="Performance" decomposition_label="and" />
  <goal id="G10.1" name="Response time must not exceed 5 seconds"
    decomposition_label="and" />
  <goal id="G10.2" name="Capability to handle 20 simultaneous users"
    decomposition_label="and" />
- <correlation_relationship label="help">
  - <source>
    <goal_ref id="G10.1" decomposition_label="and" />
  </source>
  - <target>
    <softgoal_ref id="S10.1" decomposition_label="and" />
  </target>

```

```

</correlation_relationship>
- <correlation_relationship label="help">
  - <source>
    <goal_ref id="G10.2" decomposition_label="and" />
  </source>
  - <target>
    <softgoal_ref id="S10.1" decomposition_label="and" />
  </target>
</correlation_relationship>
- <correlation_relationship label="help">
  - <source>
    <softgoal_ref id="S10.1" decomposition_label="and" />
  </source>
  - <target>
    <softgoal_ref id="G1" decomposition_label="and" />
  </target>
</correlation_relationship>
</goal_model>
- <goal_model id="GM3" name="Usability">
  - <softgoal id="S3.1" name="Usability" decomposition_label="and">
    - <softgoal id="S3.1.1" decomposition_label="make" name="Usability
      [documentation]">
      <softgoal id="S3.1.1.2" decomposition_label="make" name="Usability
        [help] available on user interface" />
    </softgoal>
    - <softgoal id="S3.1.2" decomposition_label="make" name="Usability
      [user interface]">
      - <softgoal id="S3.1.2.7" decomposition_label="help"
        name="Accessibility">
        <task id="T3.1.2.2" decomposition_label="make" name="Use
          [servlets]" />
      </softgoal>
    </softgoal>
  </softgoal>
  - <softgoal id="S3.2" decomposition_label="make" name="Configurability">
    - <correlation_relationship label="help">
      - <source>
        <softgoal_ref id="S3.2" decomposition_label="and" />
      </source>
      - <target>
        <softgoal_ref id="S3.1" decomposition_label="and" />
      </target>
    </correlation_relationship>
  </softgoal>
  - <correlation_relationship label="help">
    - <source>
      <softgoal_ref id="S3.1" decomposition_label="and" />
    </source>
    - <target>
      <softgoal_ref id="G1" decomposition_label="and" />
    </target>
  </correlation_relationship>
</goal_model>
</aspect_oriented_model>

```